

When it rains, Marathon shines!

PRODUCT LINE CARD

DRAINS VENTS & BREATHERS DRAIN REPLACEMENT PARTS ACCESSORIES ROOFING & SHEET METAL EQUIPMENT SAFETY



marathondrains.com | P 800.828.8424 | F 716.332.7676

DRAINS • VENTS • ACCESSORIES • EQUIPMENT • PEDESTAL SUPPORTS

Retrofit Drains

Aluminum • Copper • Stainless Steel • Galvanized • Plastic



Direct Connect Drains

Aluminum • Copper • PVC • Cast Iron



Vents & Breathers

Aluminum • PVC • TPO



PRODUCT SPECIFICATIONS	OVERALL HEIGHT		ASE OPENING WIT		FLANGE MATERIAL	RECOMMENDED SPACING
ALUMINUM INSULVENTS	8 1/2 IN. 216MM	4 IN. 102MM	3 IN. 76MM	10 3/4 IN. 273MM	ALUMINUM	1 PER 1000 SQ. FT. 93M ²
LC VENT (LARGE CAPACITY)	8 1/2 IN. 216MM	8 IN. 203MM	6 IN. 152MM	13 IN. 330MM	ALUMINUM	1 PER 1500 SQ. FT. 139M ²
XLC (EXTRA LARGE CAPACITY)	11 1/2 IN. 292MM	12 1/2 IN. 317MM	N/A	17 1/4 IN. 438MM	ALUMINUM	1 PER 2000 SQ. FT. 186M ²
MC VENT (MEDIUM CAPACITY)	9 1/2 IN. 241MM	6 1/2 IN. 165MM	5 3/8 IN. 136MM	10 IN. 254MM	ALUMINUM	1 PER 1500 SQ. FT. 139M ²
PRE VENT (LARGE CAPACITY)	9 IN. 229MM	10 1/4 IN. 254MM	N/A	14 3/4 IN. 375MM	PVC	1 PER 2000 SQ. FT. 186M ²
EX-FLOW INSULATION VENT	8 IN. 203MM	5 1/4 IN. 133MM	N/A	10 1/2 IN. 267MM	HDPE OR PVC	1 PER 1000 SQ. FT. 93M ²
M-105 INSULATION BREATHER	8 IN. 203MM	5 1/4 IN. 133MM	N/A	10 1/2 IN. 267MM	HDPE OR PVC	1 PER 1000 SQ. FT. 93M ²

Breather & Vent General Installation Instructions:

General installation instructions for BUR:

- 1. Select a location over an insulation joint
- 2. Cut a 4" hole through felts & insulation (Make sure that the vapor barrier is no punctured)
- 3. Center the vent over the opening, making sure that the opening is free of debris and set in asphalt cement
- 4. Flash base flange with 2 ply's of felt and asphalt cement (Extend first ply 6" beyond flange and second 9")
- 5. Pour flood coat of asphalt to base of roof vent
- 6. For other roofing systems follow manufactures' specifications

For further Technical Information or the Name of your Nearest Distributor, Call Toll Free at 1.800.828.8424

Accessories



CAN'T FIND WHAT YOU NEED? JUST ASK US!

800.828.8424 • MARATHONDRAINS.COM

Drain Replacement Parts



Safety



includes a harness, rope grab with a 2' energy absorber, anchorage connector and a 25' or 50' lifeline all housed in a 5 gallon storage pail. The kit is fully customizable with a variety of rope lengths and anchor options, and is ideal for nearly any roofing job.

CAN'T FIND WHAT YOU NEED? JUST ASK US!

800.828.8424 MARATHONDRAINS.COM

Equipment



CAN'T FIND WHAT YOU NEED? JUST ASK US!

800.828.8424 MARATHONDRAINS.COM



