



8"ALUMINATOR

ALL ALUMINUM RETROFIT ROOF DRAIN WITH PROMAXX SEAL

FEATURES:

- All Aluminum Retrofit Drain with Aluminum Body
- Standard with ProMaxx Rubber Seal
- Larger Stud Diameterfor Increased strength
- Heavy Duty Aluminum Ring that is 1-1/4" Tall
 12 Scallops to Maximize Drainage
 Seep Holes on Bottom of Ring & Bolt in Place
 3 Bolt Aluminum Strainer that is 10" Diameter x 6" Tall)
- Constructed of Heavy Duty Spun Aluminum for Quick & Easy Installation
- ProMaxx Seal Prevents Water Back-up Issues
- Flange Diameter 16" Drain Outlet Length 12"
- Available 22" long outlet

OPTIONS/ACCESSORIES

- OVERFLOW RING Aluminum Overflow Ring
- 2.75" LOW PROFILE ALUMINUM STRAINER
- PVC/TPO COATINGS

Our Aluminator Flange has the option to be PVC or TPO Coated for direct hot air welding of PVC and TPO type roofing membranes.



Low profile aluminum strainer









Aluminator with overflow ring

Due to variations in manufacturing and job site inconsistencies the above data are guidelines only and are not guaranteed for any specific situations.



PVC coating only

