



8"ALUMINATOR

ALL ALUMINUM RETROFIT ROOF DRAIN w PROMAXX SEAL

FEATURES:

- All Aluminum Retrofit Drain with Aluminum Body
- Standard with ProMaxx Rubber Seal
- Larger Stud Diameter for Increased
- Heavy Duty Aluminum Ring that is 1-1/4" Tall
 12 Scallops to Maximize Drainage
 Seep Holes on Bottom of Ring & Bolt in Place
 3 Bolt Aluminum Strainer that is 10" Diameter x 6" Tall)
- Constructed of Heavy Duty Spun Aluminum for Quick & Easy Installation
- Supplied with 8" ProMaxx Seal
- ProMaxx Seal Prevents Water Back-up Issues
- Flange Diameter 16" Drain Outlet Length 12"



OVERFLOW RING

Marathon Roofing Product's Overflow option is a spun aluminum attachment that is designed to use with all of our aluminum drains with clamping ring. It provides additional drainage when water levels exceeds 2 inches. 2" & 4" aluminum overflow insert available (call for details)

- 2.75" LOW PROFILE ALUMINUM STRAINER
- PVC/TPO COATINGS

Our Aluminator Flange has the option to be PVC or TPO Coated for direct hot air welding of PVC and TPO type roofing membranes.



Low profile aluminum strainer











Due to variations in manufacturing and job site inconsistencies the above data are guidelines only and are not guaranteed for anyspecific situations.



