



Dektite® Premium

More Flexible sizing
for better coverage



- ☒ Low profile base with watershed sleeve
Improves water run off and protects silicone sealant
- ☒ Larger square base will cover a larger opening
So more forgiving for penetration openings and allows for steeper roof pitch
- ☒ Unique cone design
Provides 10mm (1/2") continuous contact with flashed pipe providing a watertight seal
- ☒ Clear markings in metric and imperial measurements
Makes for easier cutting to pipe size
- ☒ Size Ranges - Numbers 0-9
Available in Black and Grey EPDM, and Red Silicone
- ☒ Twenty year warranty
Just fit it and forget it - we've got you covered

Selection Guide

DEKS Code- Stock is Black (Special order in Grey or Red Silicone)			Description	Pipe OD		Base		Pitch	Carton QTY	Marathon Part # (FOR BLACK EPDM)
Black EPDM	Grey EPDM	Red Silicone		mm	inch	mm	inch			
DFE10MB	DFE10MG	DFE20MRE	Dektite Premium Micro	0 - 20	0 - ¾"	71 x 71	2 ¾ x 2 ¾"	0-45° or 12/12	20	C12-01121
DFE100B	DFE100G	DFE200RE	Dektite Premium #0	0 - 35	0 - 1½"	100 x 100	4 x 4"	0-45° or 12/12	20	C12-01122
DFE100BS	DFE100GS	DFE200RES	Dektite Premium #0 Solar	0 - 35	0 - 1½"	100 x 100	4 x 4"	0-45° or 12/12	20	C12-01123
DFE101B	DFE101G	DFE201RE	Dektite Premium #1	0 - 55	¼ - 2 ¼"	139 x 139	5 ½ x 5 ½"	0-45° or 12/12	15	C12-0112
DFE101BS	DFE101GS	DFE201RES	Dektite Premium #1 Solar	5 - 55	¼ - 2 ¼"	139 x 139	5 ½ x 5 ½"	0-45° or 12/12	15	C12-01124
DFE102B	DFE102G	DFE202RE	Dektite Premium #2	5 - 76	¼ - 3"	178 x 178	7 x 7"	0-45° or 12/12	15	C12-0113
DFE102BA	DFE102GA	DFE202REA	Dektite Premium 50-70	50 - 70	2 - 2 ¾"	178 x 178	7 x 7"	0-45° or 12/12	15	C12-01125
DFE103B	DFE103G	DFE203RE	Dektite Premium #3	5 - 127	¼ - 5"	221 x 221	8 ¾ x 8 ¾"	0-45° or 12/12	15	C12-0114
DFE104B	DFE104G	DFE204RE	Dektite Premium #4	75 - 175	3 - 7"	280 x 280	11 x 11"	0-45° or 12/12	10	C12-0115
DFE105B	DFE105G	DFE205RE	Dektite Premium #5	100 - 200	4 - 8"	310 x 310	12 ½ x 12 ½"	0-45° or 12/12	10	C12-0116
DFE106B	DFE106G	DFE206RE	Dektite Premium #6	125 - 230	5 - 9"	363 x 363	14 ¼ x 14 ¼"	0-45° or 12/12	10	C12-0117
DFE107B	DFE107G	DFE207RE	Dektite Premium #7	150 - 300	6 - 12"	456 x 456	18 x 18"	0-45° or 12/12	10	C12-0120
DFE108B	DFE108G	DFE208RE	Dektite Premium #8	170 - 355	6 ¾ - 14"	496 x 496	19 ½ x 19 ½"	0-45° or 12/12	5	C12-0122
DFE109B	DFE109G	DFE209RE	Dektite Premium #9	230 - 508	9 - 20"	681 x 681	26 ¾ x 26 ¾"	0-45° or 12/12	5	C12-0124

Available in Black and Grey EPDM or Red Silicone

EPDM will withstand constant temperatures at the roofline of -50°C (-58°F) to 115°C (239°F) and up to 150°C (302°F) intermittently
Red Silicone will withstand constant temperatures at the roofline of -50°C (-58°F) to 200°C (392°F) and up to 250°C (482°F) intermittently

Please Note That the outside temperature of the pipe may be significantly different to the exit temperature of the appliance.

Installation Information



1 Trim the cone to suit pipe size using sharp tin snips.



2 Slide down pipe using water as a lubricant.



3 Apply sealant by turning back flexible flange.



4 Press base to the roof profile by hand. Smooth out any awkward creases. Don't fully extend to allow for vibration.



5 Fasten using self-sealing fasteners or pop (sealed) rivets.



* A Dektite may be fitted on the 'diamond' for enlarged holes and penetrations on steep pitched roofs up to 45° or deep corrugations

- Always use the neutral cure low modulus silicone for sealing
- In corrosive and coastal environments fix using blind aluminium rivets

Need to flash a tiled roof? Contact DEKS to discuss the tile roof flashing range.