

# ECONOMY CENTURY SERIES ROOF DRAINS

**FOR NEW & RE-ROOFING APPLICATIONS**

**OPTIONS:**

**Flange Surface:**

State suffix based on roofing system used:

- PRIMED for BUR and MODIFIED BITUMEN;
- PVC or TPO coated systems. Use Plain finish for EPDM systems.

**Strainers: Cast Iron 10", Aluminum strainer 10"**

**SPECIFICATIONS:**

**Flange:** 14" diameter 16 oz. copper

**Coating:** Asphalt primed for BUR and Modified, PVC coated for PVC membranes, no coating for EPDM or Hypalon membranes

**Clamping Ring:** Recommended for Single Ply & TPO membranes

**Strainer Dome:** High density polyethylene, 10" in diameter


**Drain Connections:** Straight or 90° Fernco XJ couplings for PVC/ABS, cast iron or copper pipe



**CS49  
Economy  
Straight  
14" Flange  
10" Strainer**



**CS49CR (E)  
Economy  
14" Flange,  
10" Strainer  
& Clamping Ring**



**PVC Coating  
Only**

**MANUFACTURER/WARRANTY**

Marathon Roofing Products offers more than 50 years experience supplying the roofing industry with quality roof drains, vents, breathers and roof accessories. Products for both new and replacement roofing are adaptable to all roof systems to provide reliable and long life performance.

Drains for new construction include The Century Premium and Century Economy models. They are designed for direct connection to downpipes with expansion or rigid connectors. Marathon roof drain assemblies can also be custom fabricated to meet almost any situation.

Marathon products are inspected and warranted. Any product proven to be defective within one year of installation will be replaced or cost price refunded, at the Company's option, subject to minor limitations.

CENTURY STRAIGHT STYLE						OUTLET DIMENSIONS					
Drain	Pipe Size	Cat #	Specification	Flange	Size	Inside	Diameter	Outside	Diameter	Overall	Length
2"	51 mm	CS29	CS 200x9	14"	356 mm	2"	51 mm	2.125"	54 mm	9"	229 mm
3"	76 mm	CS39	CS 300x9	14"	356 mm	3"	76 mm	3.125"	79 mm	9"	229 mm
4"	102 mm	CS49	CS 400x9	14"	356 mm	4"	102 mm	4.125"	105 mm	9"	229 mm
2"	51 mm	CS29 CR(E)	CS 200x9 CR(SF)	14"	356 mm	2"	51 mm	2.125"	54 mm	9"	229 mm
3"	76 mm	CS39 CR(E)	CS 300x9 CR(SF)	14"	356 mm	3"	76 mm	3.125"	79 mm	9"	229 mm
4"	102 mm	CS49 CR(E)	CS 400x9 CR(SF)	14"	356 mm	4"	102 mm	4.125"	105 mm	9"	229 mm

\* Longer length available upon request.